Forest Products Journal Index . . . 1971

Articles are listed in three ways: by title, by subject, and by author. Combined title and subject listings appear first. Titles are listed alphabetically, with leading articles *A, An,* and *The* omitted. Whenever possible, subject listings are grouped under 11 subject-matter divisions, with the division title printed in boldface capital letters, and appropriate subdivisions printed in upper and lower case boldface. Where appropriate, additional boldface headings have been included and many articles have been cross-referenced under several headings.

The Author Index contains an entry for every author, with complete information listed under the senior author; listings for co-authors refer back to the senior author.

Reprints of all articles listed in the index may be obtained. The reprint order number and the cost per single copy are listed in both sections. Prices are based on 20 cents per printed page, with a $1.50 maximum charge per reprint. Special bulk rates are available. Check or money order must accompany all orders.

FPRS Title and Subject Index . . . Vol. XXI, 1971

A

Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, T. L. Scroggins and R. Currier, 11:17 (No. 4634—$1.50)

ANATOMY AND FUNDAMENTAL PROPERTIES

Biological Properties

Deterioration of Southern Pine Beetle-Killed Trees, E. H. Barron, 3:57 (No. 4528—$0.60)

Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), H. D. Erickson and A. R. de Freitas, 4:53 (No. 4489—$1.20)

Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, H. W. Scheld and R. C. DeGroot, 4:33 (No. TN-216—$0.40)

Chemical Properties

Bacterial Degradation of Dye Used in Incense Cedar Pencil Slats, W. W. Wilcox, N. D. Oldham, and H. L. Rammer, 2:50 (No. 4490—$0.60)

Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, R. C. De Groot and H. W. Scheld, 10:53 (No. 4599—$0.60)

Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, G. A. Cooper, 10:44 (No. TN-222—$0.40)

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

pH Measurements for Pressure-Refined Plant-Fiber Residues, P. Chow, C. S. Walter, and J. K. Guiher, 12:50 (No. TN-224—$0.40)

pH of Southern Pine Barks, R. E. Martin and G. R. Gray, 3:49 (No. 4446—$0.80)

Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, H. E. Young, 5:56 (No. TN-215—$0.80)

Relationship Between Collapse and Extractives in Western Red Cedar, R. W. Meyer and G. M. Barton, 4:58 (No. TN-214—$0.60)

Physical Properties

Characterization of the Strength of Juvenile Wood of Loblolly Pine (*Pinus Taeda* L.), R. G. Pearson and R. C. Gilmore, 1:23 (No. 4486—$1.50)

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

Field Measured Sound Insulation of Wood-Framed Floors, J. B. Grantham and T. B. Heebink, 5:33 (No. 4502—$1.20)

Measuring Wood Surface Smoothness: A Proposed Method, C. Peters and A. Mergen, 7:28 (No. 4602—$0.60)

Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, J. H. G. Smith and A. Kozak, 2:38 (No. TN-205—$0.60)

Usefulness of a New Method for Measuring Smoke Yield from Wood Species and Panel Products, J. J. Brenden, 12:22 (No. 4636—$1.40)

Wood Minesweepers Are Sound After 15 Years of Service, T. L. Highly, T. C. Scheffer, and M. L. Selbo, 5:46 (No. 4543—$0.60)

Aspen and Paper Birch Mixtures as Raw Material for Particleboard, C. L. Stayton, M. J. Hyvarinen, R. O. Gertjejansen, and J. G. Haygreen, 12:29 (No. 4618—$0.40)

Automatic Programing and Control for Steam-Heated Lumber Dry Kilns, E. M. Wengert and P. G. Evans, 2:56 (No. 4526—$0.80)

B

Bacterial Degradation of Dye Used in Incense Cedar Pencil Slats, W. W. Wilcox, N. D. Oldham, and H. L. Rammer, 2:50 (No. 4490—$0.60)

Bark and Residues

Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, T. L. Scroggins and R. Currier, 11:17 (No. 4634—$1.50)

Bark-Chip Segregation: A Key to Whole-Tree Utilization, J. R. Erickson, 9:110 (No. 4600—$0.80)

Harbor Debris Can Be Salvaged, G. Pierson and F. E. Hampf, 9:79 (No. 4630—$0.60)

Hardwood Bark as a Growing Media for Container-Grown Ornamentals, J. B. Gartner, M. M. Meyer, Jr., and D. C. Saupe, 5:25 (No. 4563—$1.00)

Hardwood Bark for Packaging of Bare Root Nursery Stock, J. B. Gartner, J. E. Klett, and D. C. Saupe, 6:36 (No. 4564—$1.00)

pH Measurements for Pressure-Refined Plant-Fiber Residues, P. Chow, C. S. Walters, and J. K. Guiher, 12:50 (No. TN-224—$0.40)

Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, H. E. Young, 5:56 (No. TN-215—$0.80)

Redwood Bark Fiber in Particleboard, W. A. Dost, 10:38 (No. 4592—$1.20)

Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, J. H. G. Smith and A. Kozak, 2:38 (No. TN-205—$0.60)

Transportation Costs in Oregon for Wood and Bark Residues, P. E. Hyde and S. E. Corder, 10:17 (No. 4568—$1.50)

Utilization of Bark in Highway Landscaping, J. Mater, 8:17 (No. 4648—$0.80)

Bark-Chip Segregation: A Key to Whole-Tree Utilization, J. R. Erickson, 9:110 (No. 4600—$0.80)

Bending Strength and Moment-Rotation Characteristics of Two-Pin Moment-Resisting Dowel Joints, C. A. Eckelman, 3:35 (No. 4527—$1.00)

Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, R. C. De Groot and H. W. Scheld, 10:53 (No. 4599—$0.60)

Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, G. A. Cooper, 10:44 (No. TN-222—$0.40)

C

Characterization of the Strength of Juvenile Wood of Loblolly Pine

Forest Products Journal Index . . . 1971

Articles are listed in three ways: by title, by subject, and by author. Combined title and subject listings appear first. Titles are listed alphabetically, with leading articles *A, An,* and *The* omitted. Whenever possible, subject listings are grouped under 11 subject-matter divisions, with the division title printed in boldface capital letters, and appropriate subdivisions printed in upper and lower case boldface. Where appropriate, additional boldface headings have been included and many articles have been cross-referenced under several headings.

The Author Index contains an entry for every author, with complete information listed under the senior author; listings for co-authors refer back to the senior author.

Reprints of all articles listed in the index may be obtained. The reprint order number and the cost per single copy are listed in both sections. Prices are based on 20 cents per printed page, with a $1.50 maximum charge per reprint. Special bulk rates are available. Check or money order must accompany all orders.

FPRS Title and Subject Index . . . Vol. XXI, 1971

A

Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, T. L. Scroggins and R. Currier, 11:17 (No. 4634—$1.50)

ANATOMY AND FUNDAMENTAL PROPERTIES

Biological Properties

Deterioration of Southern Pine Beetle-Killed Trees, E. H. Barron, 3:57 (No. 4528—$0.60)

Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), H. D. Erickson and A. R. de Freitas, 4:53 (No. 4489—$1.20)

Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, H. W. Scheld and R. C. DeGroot, 4:33 (No. TN-216—$0.40)

Chemical Properties

Bacterial Degradation of Dye Used in Incense Cedar Pencil Slats, W. W. Wilcox, N. D. Oldham, and H. L. Rammer, 2:50 (No. 4490—$0.60)

Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, R. C. De Groot and H. W. Scheld, 10:53 (No. 4599—$0.60)

Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, G. A. Cooper, 10:44 (No. TN-222—$0.40)

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

pH Measurements for Pressure-Refined Plant-Fiber Residues, P. Chow, C. S. Walter, and J. K. Guiher, 12:50 (No. TN-224—$0.40)

pH of Southern Pine Barks, R. E. Martin and G. R. Gray, 3:49 (No. 4446—$0.80)

Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, H. E. Young, 5:56 (No. TN-215—$0.80)

Relationship Between Collapse and Extractives in Western Red Cedar, R. W. Meyer and G. M. Barton, 4:58 (No. TN-214—$0.60)

Physical Properties

Characterization of the Strength of Juvenile Wood of Loblolly Pine (*Pinus Taeda* L.), R. G. Pearson and R. C. Gilmore, 1:23 (No. 4486—$1.50)

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

Field Measured Sound Insulation of Wood-Framed Floors, J. B. Grantham and T. B. Heebink, 5:33 (No. 4502—$1.20)

Measuring Wood Surface Smoothness: A Proposed Method, C. Peters and A. Mergen, 7:28 (No. 4602—$0.60)

Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, J. H. G. Smith and A. Kozak, 2:38 (No. TN-205—$0.60)

Usefulness of a New Method for Measuring Smoke Yield from Wood Species and Panel Products, J. J. Brenden, 12:22 (No. 4636—$1.40)

Wood Minesweepers Are Sound After 15 Years of Service, T. L. Highly, T. C. Scheffer, and M. L. Selbo, 5:46 (No. 4543—$0.60)

Aspen and Paper Birch Mixtures as Raw Material for Particleboard, C. L. Stayton, M. J. Hyvarinen, R. O. Gertjejansen, and J. G. Haygreen, 12:29 (No. 4618—$0.40)

Automatic Programing and Control for Steam-Heated Lumber Dry Kilns, E. M. Wengert and P. G. Evans, 2:56 (No. 4526—$0.80)

B

Bacterial Degradation of Dye Used in Incense Cedar Pencil Slats, W. W. Wilcox, N. D. Oldham, and H. L. Rammer, 2:50 (No. 4490—$0.60)

Bark and Residues

Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, T. L. Scroggins and R. Currier, 11:17 (No. 4634—$1.50)

Bark-Chip Segregation: A Key to Whole-Tree Utilization, J. R. Erickson, 9:110 (No. 4600—$0.80)

Harbor Debris Can Be Salvaged, G. Pierson and F. E. Hampf, 9:79 (No. 4630—$0.60)

Hardwood Bark as a Growing Media for Container-Grown Ornamentals, J. B. Gartner, M. M. Meyer, Jr., and D. C. Saupe, 5:25 (No. 4563—$1.00)

Hardwood Bark for Packaging of Bare Root Nursery Stock, J. B. Gartner, J. E. Klett, and D. C. Saupe, 6:36 (No. 4564—$1.00)

pH Measurements for Pressure-Refined Plant-Fiber Residues, P. Chow, C. S. Walters, and J. K. Guiher, 12:50 (No. TN-224—$0.40)

Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, H. E. Young, 5:56 (No. TN-215—$0.80)

Redwood Bark Fiber in Particleboard, W. A. Dost, 10:38 (No. 4592—$1.20)

Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, J. H. G. Smith and A. Kozak, 2:38 (No. TN-205—$0.60)

Transportation Costs in Oregon for Wood and Bark Residues, P. E. Hyde and S. E. Corder, 10:17 (No. 4568—$1.50)

Utilization of Bark in Highway Landscaping, J. Mater, 8:17 (No. 4648—$0.80)

Bark-Chip Segregation: A Key to Whole-Tree Utilization, J. R. Erickson, 9:110 (No. 4600—$0.80)

Bending Strength and Moment-Rotation Characteristics of Two-Pin Moment-Resisting Dowel Joints, C. A. Eckelman, 3:35 (No. 4527—$1.00)

Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, R. C. De Groot and H. W. Scheld, 10:53 (No. 4599—$0.60)

Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, G. A. Cooper, 10:44 (No. TN-222—$0.40)

C

Characterization of the Strength of Juvenile Wood of Loblolly Pine

(*Pinus Taeda* L.), R. G. Pearson, and R. C. Gilmore, 1:23 (No. 4486—$1.50)

CHEMICAL CONVERSION

Creep of Wood after Soaking in Liquid Anhydrous Ammonia, D. Green and C. Koch, 11:50 (No. TN-206—$0.40)

Gamma Irradiation Effects on Modulus of Elasticity of Engelmann Spruce, C. E. Shuler, 7:49 (No. TN-194—$0.60)

Chips Produced With a Helical Cutter, H. A. Stewart, 5:44 (No. 4253—$0.40)

Climate Index for Estimating Potential for Decay in Wood Structures Above Ground, T. C. Scheffer, 10:25 (No. 4594—$1.40)

Combining Radio-Frequency Heating with Kiln-Drying to Provide Fast Drying without Degrade, D. G. Miller, 12:17 (No. 4616—$1.00)

Computerized Economic Comparison of a Conventional Furniture Rough Mill with a New Processing System, H. A. Huber, 2:34 (No. 4509—$1.00)

Construction Grade Plywood from Grade 3 Hardwoods—An Industrial Possibility, E. P. Craft, 2:26 (No. 4455—$1.00)

Consumer Life Styles and Household Furniture Purchases, W. S. Good, 4:11 (No. 4510—$1.00)

Control of Emissions from Batch-Type Charcoal Kilns, J. R. Hartwig, 9:49 (No. 4728—$0.40)

Creep of Wood after Soaking in Liquid Anhydrous Ammonia, D. Green and C. Koch, 11:50 (No. TN-206—$0.40)

D

Deterioration of Southern Pine Beetle-Killed Trees, E. H. Barron, 3:57 (No. 4528—$0.60)

Determining Veneer Surface Inactivation by a Reflectance Colorimeter, S.-Z. Chow, 2:19 (No. 4515—$1.20)

Development of a Hardwood Utilization Complex—A New Approach, E. L. Klein, 4:16 (No. 4561—$0.60)

Developments in Roll Spreading Techniques, D. T. Jones, 6:24 (No. 4473—$1.00)

DRYING

General

Economical Humidity Jar, Its Design and Use, R. T. Lin, 7:51 (No. TN-219—$0.60)

Kiln Drying

Automatic Programing and Control for Steam-Heated Lumber Dry Kilns, E. M. Wengert and P. G. Evans, 2:56 (No. 4526—$0.80)

Drying West Coast Dimension to Meet the New Lumber Standards, E. M. Williston, 3:44 (No. 4538—$1.00)

Process for Straightening and Drying Southern Pine 2 by 4's in 24 Hours, P. Koch, 5:17 (No. 4569—$1.50)

Moisture-Use Relationship

Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, G. A. Cooper, 10:44 (No. TN-222—$0.40)

Electrical Moisture Meter Readings on Western Hemlock Dimension Lumber, C. J. Kozlik, 6:34 (No. TN-218—$0.40)

Equilibrium Moisture Content Prediction for Wood, W. T. Simpson, 5:48 (No. 4555—$0.40)

Feasibility Studies on Gluing of Red Oak at Elevated Moisture Contents, W. K. Murphey, B. E. Cutter, E. Wachsmuth, and C. Gatchell, 8:56 (No. TN-213—$0.80)

Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), H. D. Erickson and A. R. de Freitas, 4:53 (No. 4489—$1.20)

Linear Expansion of Veneered Furniture Panels, O. Suchsland, 9:90 (No. 4586—$1.40)

Plastic Soil Covers Reduce the Moisture Content in Basementless Homes, T. L. Amburgey and D. W. French, 8:43 (No. TN-212—$0.40)

Relationship Between Collapse and Extractives in Western Red Cedar, R. W. Meyer and G. M. Barton, 4:58 (No. TN-214—$0.60)

Shrinkage of Douglas-Fir, Western Hemlock, and Red Alder as Affected by Drying Conditions, L. D. Espenas, 6:44 (No. 4596—$0.60)

Sorting Southern Pine Green Veneer to Improve Drying Control, E. O. Walters, 11:52 (No. 4422—$1.50)

Steam-Bending Properties of Southern Pine, T. J. Lemoine and P. Koch, 4:34 (No. 4571—$1.50)

Special Drying Methods

Dynamic Transverse Compression Treatment to Improve Drying Behavior of Yellow Birch, M. Y. Cech, 2:41 (No. 4512—$1.50)

Combining Radio-Frequency with Kiln-Drying to Provide Fast Drying without Degrade, D. G. Miller, 12:17 (No. 4616—$1.00)

Drying 1-Inch Ponderosa Pine Lumber with a Combination of Microwave Power and Hot Air, W. R. McAlister and H. Resch, 3:26 (No. 4550—$1.50)

Effect of Resonating Wood During Drying, E. S. Kotok, 2:24 (No. 4451—$0.40)

High-Temperature Kiln-Drying of Spruce Joists, M. Y. Cech and D. R. Huffman, 10:55 (No. 4598—$1.20)

Low-Temperature Drying of 4/4 Appalachian Red Oak, D. G. Cuppett and E. P. Craft, 1:34 (No. 4475—$1.00)

Operational Variables in Press Drying Eastern Hemlock, G. A. Ziegler, W. K. Murphey, and F. C. Beall, 10:32 (No. TN-220—$0.60)

Prefreezing Alone and Combined with Presteaming in the Drying of Redwood Dimension, R. Erickson, L. Demaree, P. Johnston, and E. Morton, 7:54 (No. 4579—$1.20)

Veneer Drying

Fluidized Bed Drying of Southern Pine Veneer, W. E. Loos, 12:44 (No. 4589—$1.20)

Kinetics of Veneer Jet Drying, G. L. Comstock, 9:104 (No. 4597—$1.40)

Drying 1-Inch Ponderosa Pine Lumber with a Combination of Microwave Power and Hot Air, W. R. McAlister and H. Resch, 3:26 (No. 4550—$1.50)

Drying West Coast Dimension to Meet the New Lumber Standards, E. M. Williston, 3:44 (No. 4538—$1.00)

Durability of Water-Resisting Treatments on Wood Siding, A. F. Verrall, 6:57 (No. TN-217—$0.40)

Dynamic Transverse Compression Treatment to Improve Drying Behavior of Yellow Birch, M. Y. Cech, 2:41 (No. 4512—$1.50)

E

Economical Humidity Jar, Its Design and Use, R. T. Lin, 7:51 (No. TN-219—$0.60)

Economics of Technical Improvements or Putting R & D to Work, F. A. Tayelor, 10:9 (No. 4686—$0.60)

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

Effect of Resonating Wood During Drying, E. S. Kotok, 2:24 (No. 4451—$0.40)

Elastomeric Adhesives for Field-Gluing Plywood Floors, C. B. Vick, 8:34 (No. 4604—$1.50)

Electrical Moisture Meter Readings on Western Hemlock Dimension Lumber, C. J. Kozlik, 6:34 (No. TN-218—$0.40)

Engineered Products: See Wood Engineering.

Environment and the Forest Products Industry, S. A. Cain, 9:16 (No. 4721—$0.60)

Equilibrium Moisture Content Prediction for Wood, W. T. Simpson, 5:48 (No. 4555—$0.40)

Evaluating Particleboard Properties by Measuring Saw-Cutting Force, K. C. Shen, 10:46 (No. 4610—$1.40)

Evaluation of Machine Stress Rating Grades Assigned to Eastern Spruce Structural Lumber, A. M. Brackley and J. E. Shottafer, 4:43 (No. TN-209—$0.80)

Extractives: See Chemical Conversion.

F

Factors in Converting to 'Super' Finishes, A. W. Riedell, 5:12 (No. 4518—$0.60)

Feasibility Studies on Gluing of Red Oak at Elevated Moisture Contents, W. K. Murphey, B. E. Cutter, E. Wachsmuth, and C. Gatchell, 8:56 (No. TN-213—$0.80)

Field Measured Sound Insulation of Wood-Framed Floors, J. B. Grantham and T. B. Heebink, 5:33 (No. 4502—$1.20)

Finishing: See Treatments and Coatings.

Fluidized Bed Drying of Southern Pine Veneer, W. E. Loos, 12:44 (No. 4589—$1.20)

Force and Work to Shear Green Southern Pine Logs at Slow Speed, P. Koch, 3:21 (No. 4558—$1.20)

Forest and Forest Products Industry of the Republic of South Africa, D. P. Lombard, 10:14 (No. 4693—$0.60)

Forest Products for a Better Environment, J. I. Zerbe, 6:16 (No. 4626—$0.60)

Forest Products in Taiwan, S.-C. Wu, 8:13 (No. 4661—$0.40)

Formaldehyde Detection and Control in the Wood Industry, H. G. Freeman and W. C. Grendon, 9:54 (No. 4672—$0.80)

Fluorocarbon Resin Finishes for Wood Cutting Tools, C. I. Poole, 3:40 (No. 4498—$0.60)

G

Gamma Irradiation Effects on Modulus of Elasticity of Engelmann Spruce, C. E. Shuler, 7:49 (No. TN-194—$0.60)

GLUES AND GLUING PROCESSES

General

Developments in Roll Spreading Techniques, D. T. Jones, 6:24 (No. 4473—$1.00)

Feasibility Studies on Gluing of Red Oak at Elevated Moisture Contents, W. K. Murphey, B. E. Cutter, E.

Wachsmuth, and C. Gatchell, 8:56 (No. TN-213—$0.80)

Adhesives

Elastomeric Adhesives for Field-Gluing Plywood Floors, C. B. Vick, 8:34 (No. 4604—$1.50)

Properties of Phenolic Adhesives as Related to Bond Quality in Southern Pine Plywood, C.-Y. Hse, 1:44 (No. 4485—$1.50)

Resistance Strain Gages and Adhesives for Wood, A. Sliker, 12:40 (No. 4623—$0.80)

Glue Lam

Stresses in Curved Glued-Laminated Timber Beams: Experimental Study, R. O. Foschi, 7:42 (No. 4562—$1.40)

Tension Proof Loading of Finger Joints for Laminated Beams, M. D. Strickler and R. F. Pellerin, 6:19 (No. 4577—$1.20)

Tension Proof Loading of Lam Stock for Laminated Beams, R. F. Pellerin and M. D. Strickler, 5:50 (No. 4536—$1.20)

Overlays and Films

Performance of House Paint on Two Overlays on Cottonwood Siding, G. A. Cooper and S. H. Barham, 3:53 (No. 4546—$0.80)

Resistance of Resin-Impregnated Paper Overlays to Accelerated Weathering, D. J. Fahey and D. S. Pierce, 11:30 (No. 4603—$1.50)

Variables in Vacuum Laminating of Thermoplastic Films, T. F. Duncan, 7:30 (No. 4488—$1.50)

Veneers and Plywood

Construction Grade Plywood from Grade 3 Hardwoods—An Industrial Possibility, E. P. Craft, 2:26 (No. 4455—$1.00)

Determining Veneer Surface Inactivation by a Reflectance Colorimeter, S.-Z. Chow, 2:19 (No. 4515—$1.20)

Identifying Veneer in Recovery Studies, P. H. Lane, 6:32 (No. 4611—$0.40)

Linear Expansion of Veneered Furniture Panels, O. Suchsland, 9:90 (No. 4586—$1.40)

Properties of Phenolic Adhesives as Related to Bond Quality in Southern Pine Plywood, C.-Y. Hse, 1:44 (No. 4485—$1.50)

Scheduling and Control of a Douglas-fir Plywood Plant Aided by Linear Programming, E. W. Wellwood, 11:42 (No. 4593—$1.50)

Sorting Southern Pine Green Veneer to Improve Drying Control, E. O. Walters, 11:52 (No. 4422—$1.50)

Veneer Yields from Turpentined Slash Pine Peeler Blocks, A. Clark III and J. G. Schroeder, 2:53 (No. 4521—$1.00)

H

Handling Phenolic Resin Adhesive Wash Water in Southern Pine Plywood Plants, H. H. Haskell, 9:64 (No. 4635—$1.20)

Harbor Debris Can Be Salvaged, G. Pierson and F. E. Hampf, 9:79 (No. 4630—$0.60)

Hardwood Bark as a Growing Media for Container-Grown Ornamentals, J. B. Gartner, M. M. Meyer, Jr., and D. C. Saupe, 5:25 (No. 4563—$1.00)

Hardwood Bark for Packaging of Bare Root Nursery Stock, J. B. Gartner, J. E. Klett, and D. C. Saupe, 6:36 (No. 4564—$1.00)

High-Temperature Kiln-Drying of Spruce Joists, M. Y. Cech and D. R. Huffman, 10:55 (No. 4598—$1.20)

Hot, Dry Mouldability of Hardboard, E. L. Back, E. I. E. Didriksson, F. Johanson, and K. G. Norberg, 9:96 (No. 4595—$1.00)

I

Identifying Veneer in Recovery Studies, P. H. Lane, 6:32 (No. 4611—$0.40)

Improved Performance of Wigwam Burners, S. E. Corder and G. H. Atherton, 9:40 (No. 4731—$1.50)

Industrial Noise and Noise Exposure, F. M. Lamb, 9:84 (No. 4627—$0.80)

Industrial Noise Control Guidelines, F. M. Lamb, 11:12 (No. 4725—$1.00)

Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), H. D. Erickson and A. R. de Freitas, 4:53 (No. 4489—$1.20)

Instrumentation for 'Walsh-Healey' Noise Surveys, D. A. Bohrer, 9:88 (No. 4717—$0.40)

Investigation of the Mechanical Characteristics of Truss Plates on Fire-Retardant Treated Wood, D. H. Percival and S. K. Suddarth, 1:17 (No. 4495—$1.20)

Inventory Management — The Tool and the Need — In Lumber Production, F. J. Holemo, 1:12 (No. 4496—$1.00)

K

Kiln Drying: See Drying.

Kinetics of Veneer Jet Drying, G. L. Comstock, 9:104 (No. 4597—$1.40)

L

Laser Machining of Southern Pine, C. W. McMillin and J. E. Harry, 10:34 (No. 4716—$0.80)

Latin American Contribution to United States Forest Products Imports: Problems and Potentials for the Exporter, H. M. Gregersen, 3:16 (No. 4535—$1.00)

Lignin: See Chemical Conversion.

Linear Expansion of Veneered Furniture Panels, O. Suchsland, 9:90 (No. 4586—$1.40)

Location of Pentachlorophenol by Electron Microprobe and Other Techniques in Cellon Treated Douglas-fir, H. Resch and D. G. Arganbright, 1:38 (No. 4479—$1.00)

Logging Roads and the Federal Income Tax, W. C. Siegel, 10:12 (No. 4662—$0.60)

Low-Temperature Drying of 4/4 Appalachian Red Oak, D. G. Cuppett and E. P. Craft, 1:34 (No. 4475—$1.00)

M

MARKETING

Codes and Legislation

Logging Roads and the Federal Income Tax, W. C. Siegel, 10:12 (No. 4662—$0.60)

Distribution and Consumption

Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, T. L. Scroggins and R. Currier, 11:17 (No. 4634—$1.50)

Consumer Life Styles and Household Furniture Purchases, W. S. Good, 4:11 (No. 4510—$1.00)

Hardwood Bark as a Growing Media for Container-Grown Ornamentals, J. B. Gartner, M. M. Meyer, Jr., and D. C. Saupe, 5:25 (No. 4563—$1.00)

Hardwood Bark for Packaging of Bare Root Nursery Stock, J. B. Gartner, J. E. Klett, and D. C. Saupe, 6:36 (No. 4564—$1.00)

Latin American Contribution to United States Forest Products Imports: Problems and Potentials for the Exporter, H. M. Gregersen, 3:16 (No. 4535—$1.00)

Role of Forecasting in the Forest Industries, W. McKillop, 8:10 (No. 4619—$0.60)

Utilization of Bark in Highway Landscaping, J. Mater, 8:17 (No. 4648—$0.80)

Wood Products Use Trends in FHA-Inspected Single-Family Houses, R. B. Phelps, 7:10 (No. 4556—$0.80)

Promotion and Education

Environment and the Forest Products Industry, S. A. Cain, 9:16 (No. 4721—$0.60)

Forest and Forest Products Industry of the Republic of South Africa, D. P. Lombard, 10:14 (No. 4693—$0.60)

Forest Products for a Better Environment, J. I. Zerbe, 6:16 (No. 4626—$0.60)

Forest Products in Taiwan, S.-C. Wu, 8:13 (No. 4661—$0.40)

Plastics and the Future of the Furniture Industry in the United States, E. L. Clark, 8:14 (No. 4638—$0.60)

Potential of Building with Wood in South America, E. G. Stern, 7:14 (No. 4609—$0.80)

Productivity Gains in Forest Products Industries, H. F. Kaiser, Jr., 5:14 (No. 4587—$0.60)

Structural Design Manual for Furniture, C. A. Eckelman, 11:11 (No. 4353—$0.20)

Wood Housing: A World-Wide Look, H. O. Fleischer, 12:12 ($0.40)

Wood Industries and Research in the Netherlands, K. Griffioen, 5:11 (No. 4659—$0.40)

Wood Industries and Wood Science in Norway, R. Birkeland, 1:10 (No. 4591—$0.40)

Measuring Wood Surface Smoothness: A Proposed Method, C. Peters and A. Mergen, 7:28 (No. 4602—$0.60)

MECHANICAL CONVERSION

General

Measuring Wood Surface Smoothness: A Proposed Method, C. Peters and A. Mergen, 7:28 (No. 4602—$0.60)

Operations Research Application to Furniture Round Production, C. A. Fasick and J. D. Lawrence, 4:46 (No. 4545—$1.40)

Machining

Chips Produced With a Helical Cutter, H. A. Stewart, 5:44 (No. 4253—$0.40)

Force and Work to Shear Green Southern Pine Logs at Slow Speed, P. Koch, 3:21 (No. 4558—$1.20)

Laser Machining of Southern Pine, C. W. McMillin and J. E. Harry, 10:34 (No. 4716—$0.80)

Bark-Chip Segregation: A Key to Whole-Tree Utilization, J. R. Erickson, 9:110 (No. 4600—$0.80)

Computerized Economic Comparison of a Conventional Furniture Rough Mill with a New Processing System, H. A. Huber, 2:34 (No. 4509—$1.00)

Development of a Hardwood Utilization Complex — A New Approach, E. L. Klein, 4:16 (No. 4561—$0.60)

Fluorocarbon Resin Finishes for Wood Cutting Tools, C. I. Poole, 3:40 (No. 4498—$0.60)

Sawing

Evaluating Particleboard Properties by Measuring Saw-Cutting Force, K. C. Shen, 10:46 (No. 4610—$1.40)

Some Engineering Considerations of High-Strain Band Saws, A. W. Porter, 4:24 (No. 4570—$1.50)

Veneer Cutting

Construction Grade Plywood from Grade 3 Hardwoods—An Industrial Possibility, E. P. Craft, 2:26 (No. 4455—$1.00)

Identifying Veneer in Recovery Studies, P. H. Lane, 6:32 (No. 4611—$0.40)

Veneer Yields from Turpentined Slash Pine Peeler Blocks, A. Clark III and J. G. Schroeder, 2:53 (No. 4521—$1.00)

Moisture-Use Relationship: See Drying.

N

Nail Withdrawal Resistance in Plantation Red Pine Grown in Indiana, R. H. Perkins, 6:29 (No. 4575—$0.80)

Noise in the Woodworking Industry—A Review of the Literature, J. H. Smith, 9:82 (No. 4718—$0.40)

O

Operational Variables in Press Drying Eastern Hemlock, G. A. Ziegler, W. K. Murphey, and F. C. Beall, 10:32 (No. TN-220—$0.60)

Operations Research Application to Furniture Round Production, C. A. Fasick and J. D. Lawrence, 4:46 (No. 4545—$1.40)

P

PARTICLE AND FIBER PROCESSES

Hardboard

Hot, Dry Mouldability of Hardboard, E. L. Back, E. I. E. Didriksson, F. Johanson, and K. G. Norberg, 9:96 (No. 4595—$1.00)

Selection and Field Testing of Coatings for Exterior Hardboard Products, D. G. Gluck, 11:24 (No. 4401—$1.20)

Particleboard

Aspen and Paper Birch Mixtures as Raw Material for Particleboard, C. L. Stayton, M. J. Hyvarinen, R. O. Gertjejansen, and J. G. Haygreen, 12:29 (No. 4618—$0.40)

Chips Produced With a Helical Cutter, H. A. Stewart, 5:44 (No. 4253—$0.40)

Evaluating Particleboard Properties by Measuring Saw-Cutting Force, K. C. Shen, 10:46 (No. 4610—$1.40)

Physical and Mechanical Variations in Cottonwood and Hickory Flakeboards Made from Flakes of Three Sizes, S. Bhagwat, 9:101 (No. 4419—$0.60)

Quantitative Study of Some Factors Affecting the Abrasiveness of Particleboard, R. R. Bridges, 11:39 (No. 4494—$0.90)

Rapid Accelerated-Aging Test Procedure for Phenolic Particleboard, K. C. Shen and B. Wrangham, 5:30 (No. 4516—$0.80)

Redwood Bark Fiber in Particleboard, W. A. Dost, 10:38 (No. 4592—$1.20)

Relationships Between Torsion Shear and Other Strength Properties of Particleboard, K. C. Shen, 6:40 (No. 4484—$0.80)

Some Characteristics of Particleboards from Four Tropical Hardwoods of Central America, J. G. Haygreen and D. W. French, 2:30 (No. 4525—$0.80)

Torsion Shear Test for Particleboard Adapted to a Universal Testing Machine, R. Gertjejansen and J. Haygreen, 11:59 (No. TN-221—$0.40)

Performance of Eastern Hemlock Wharf Timbers, J. Krzyzewski and J. K. Shields, 3:42 (No. TN-208—$0.40)

Performance of House Paint on Two Overlays on Cottonwood Siding, G. A. Cooper and S. H. Barham, 3:53 (No. 4546—$0.80)

pH Measurements for Pressure-Refined Plant-Fiber Residues, P. Chow, C. S. Walters, and J. K. Guiher, 12:50 (No. TN-224—$0.40)

pH of Southern Pine Barks, R. E. Martin and G. R. Gray, 3:49 (No. 4446—$0.80)

Physical and Mechanical Variations in Cottonwood and Hickory Flakeboards Made from Flakes of Three Sizes, S. Bhagwat, 9:101 (No. 4419—$0.60)

Plastic Soil Covers Reduce the Moisture Content in Basementless Homes, T. L. Amburgey and D. W. French, 8:43 (No. TN-212—$0.40)

Plastics and the Future of the Furniture Industry in the United States, E. L. Clark, 8:14 (No. 4638—$0.60)

Plywood: See Glues and Gluing Processes.

Plywood and Sawmill Liquid Waste Disposal, J. R. Boydston, 9:58 (No. 4605—$1.20)

Pollution Abatement and Control

Control of Emissions from Batch-Type Charcoal Kilns, J. R. Hartwig, 9:49 (No. 4728—$0.40)

Environment and the Forest Products Industry, S. A. Cain, 9:16 (No. 4721—$0.60)

Formaldehyde Detection and Control in the Wood Industry, H. G. Freeman and W. C. Grendon, 9:54 (No. 4672—$0.80)

Handling Phenolic Resin Adhesive Wash Water in Southern Pine Plywood Plants, H. H. Haskell, 9:64 (No. 4635—$1.20)

Harbor Debris Can Be Salvaged, G. Pierson and F. E. Hampf, 9:79 (No. 4630—$0.60)

Improved Performance of Wigwam Burners, S. E. Corder and G. H. Atherton, 9:40 (No. 4731—$1.50)

Industrial Noise and Noise Exposure, F. M. Lamb, 9:84 (No. 4627—$0.80)

Industrial Noise Control Guidelines, F. M. Lamb, 11:12 (No. 4725—$1.00)

Instrumentation for 'Walsh-Healey' Noise Surveys, D. A. Bohrer, 9:88 (No. 4717—$0.40)

Noise in the Woodworking Industry—A Review of the Literature, J. H. Smith, 9:82 (No. 4718—$0.40)

Plywood and Sawmill Liquid Waste Disposal, J. R. Boydston, 9:58 (No. 4605—$1.20)

Pollution Control Activities at Georgia-Pacific, V. J. Tretter, Jr., 9:37 (No. 4617—$0.60)

Pollution Control in the Wood Preserving Industry, Part I. Nature and Scope of the Problem, W. S. Thompson and J. V. Dust, 9:70 (No. 4729—$1.20)

Principal Pollution Problems Facing the Solid Wood Products Industry, Wood Products Sub-Council, 9:33 (No. 4720—$0.80)

Soil Percolation and/or Irrigation of Industrial Effluent Waters—Especially Wood Treating Plant Effluents, C. W. Fisher, 9:76 (No. 4722—$0.80)

Veneer Dryer Emissions—Problem Definition, D. H. Brown, 9:51 (No. 4719—$0.60)

Pollution Control Activities at Georgia-Pacific, V. J. Tretter, Jr., 9:37 (No. 4617—$0.60)

Pollution Control in the Wood Preserving Industry, Part I. Nature and Scope of the Problem, W. S. Thompson and J. V. Dust, 9:70 (No. 4729—$1.20)

Potential of Building with Wood in South America, E. G. Stern, 7:14 (No. 4609—$0.80)

Predicting by Sonic Measurements the Strength of Logs and Poles Having Internal Decay, J. E. Breeze and R. H. Nilberg, 5:39 (No. 4390—$1.00)

Prefreezing Alone and Combined with Presteaming in the Drying of Redwood Dimension, R. Erickson, L. Demaree, P. Johnston, and E. Morton, 7:54 (No. 4579—$1.20)

Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, H. E. Young, 5:56 (No. TN-215—$0.80)

Preservation: See Treatments and Coatings.

Principal Pollution Problems Facing the Solid Wood Products Industry, Wood Products Sub-Council, 9:33 (No. 4720—$0.80)

Process for Straightening and Drying Southern Pine 2 by 4's in 24 Hours, P. Koch, 5:17 (No. 4569—$1.50)

PRODUCTION MANAGEMENT

Materials Handling

Developments in Roll Spreading Techniques, D. T. Jones, 6:24 (No. 4473—$1.00)

Production Control

Inventory Management — The Tool and the Need — In Lumber Production, F. J. Holemo, 1:12 (No. 4496—$1.00)

Operations Research Application to Furniture Round Production, C. A. Fasick and J. D. Lawrence, 4:46 (No. 4545—$1.40)

Scheduling and Control of a Douglas-fir Plywood Plant Aided by Linear Programming, E. W. Wellwood, 11:42 (No. 4593—$1.50)

Production Economics

Computerized Economic Comparison of a Conventional Furniture Rough Mill with a New Processing System, H. A. Huber, 2:34 (No. 4509—$1.00)

Construction Grade Plywood from Grade 3 Hardwoods—An Industrial Possibility, E. P. Craft, 2:26 (No. 4455—$1.00)

Development of a Hardwood Utilization Complex—A New Approach, E. L. Klein, 4:16 (No. 4561—$0.60)

Economics of Technical Improvements or Putting R & D to Work, F. A. Tayelor, 10:9 (No. 4686—$0.60)

Transportation Costs in Oregon for Wood and Bark Residues, P. E. Hyde and S. E. Corder, 10:17 (No. 4568—$1.50)

Productivity Gains in Forest Products Industries, H. F. Kaiser, Jr., 5:14 (No. 4587—$0.60)

Properties of Phenolic Adhesives as Related to Bond Quality in Southern Pine Plywood, C.-Y. Hse, 1:44 (No. 4485—$1.50)

XUM

Pulping: See Chemical Conversion.

Q

Quantitative Study of Some Factors Affecting the Abrasiveness of Particleboard, R. R. Bridges, 11:39 (No. 4494—$0.90)

R

Rapid Accelerated-Aging Test Procedure for Phenolic Particleboard, K. C. Shen and B. Wrangham, 5:30 (No. 4516—$0.80)

Redwood Bark Fiber in Particleboard, W. A. Dost, 10:38 (No. 4592—$1.20)

Relationship Between Collapse and Extractives in Western Red Cedar, R. W. Meyer and G. M. Barton, 4:58 (No. TN-214—$0.60)

Relationships Between Torsion Shear and Other Strength Properties of Particleboard, K. C. Shen, 6:40 (No. 4484—$0.80)

Resistance of Resin-Impregnated Paper Overlays to Accelerated Weathering, D. J. Fahey and D. S. Pierce, 11:30 (No. 4603—$1.50)

Resistance Strain Gages and Adhesives for Wood, A. Sliker, 12:40 (No. 4623—$0.80)

Role of Forecasting in the Forest Industries, W. McKillop, 8:10 (No. 4619—$0.60)

S

Scheduling and Control of a Douglas-fir Plywood Plant Aided by Linear Programming, E. W. Wellwood, 11:42 (No. 4593—$1.50)

Selection and Field Testing of Coatings for Exterior Hardboard Products, D. G. Gluck, 11:24 (No. 4401—$1.20)

Shrinkage of Douglas-Fir, Western Hemlock, and Red Alder as Affected By Drying Conditions, L. D. Espenas, 6:44 (No. 4596—$0.60)

Soil Percolation and/or Irrigation of Industrial Effluent Waters—Especially Wood Treating Plant Effluents, C. W. Fisher, 9:76 (No. 4722—$0.80)

Some Characteristics of Particleboards from Four Tropical Hardwoods of Central America, J. G. Haygreen and D. W. French, 2:30 (No. 4525—$0.80)

Some Engineering Considerations of High-Strain Band Saws, A. W. Porter, 4:24 (No. 4570—$1.50)

Sorting Southern Pine Green Veneer to Improve Drying Control, E. O. Walters, 11:52 (No. 4422—$1.50)

Southern Pine

Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, R. C. De Groot and H. W. Scheld, 10:53 (No. 4599—$0.60)

Characterization of the Strength of Juvenile Wood of Loblolly Pine (*Pinus Taeda* L.), R. G. Pearson and R. C. Gilmore, 1:23 (No. 4486—$1.50)

Deterioration of Southern Pine Beetle-Killed Trees, E. H. Barron, 3:57 (No. 4528—$0.60)

Fluidized Bed Drying of Southern Pine Veneer, W. E. Loos, 12:44 (No. 4589—$1.20)

Force and Work to Shear Green Southern Pine Logs at Slow Speed, P. Koch, 3:21 (No. 4558—$1.20)

Laser Machining of Southern Pine, C. W. McMillin and J. E. Harry, 10:34 (No. 4716—$0.80)

pH of Southern Pine Barks, R. E. Martin and G. R. Gray, 3:49 (No. 4446—$0.80)

Process for Straightening and Drying Southern Pine 2 by 4's in 24 Hours, P. Koch, 5:17 (No. 4569—$1.50)

Properties of Phenolic Adhesives as Related to Bond Quality in Southern Pine Plywood, C.-Y. Hse, 1:44 (No. 4485—$1.50)

Sorting Southern Pine Green Veneer to Improve Drying Control, E. O. Walters, 11:52 (No. 4422—$1.50)

Steam-Bending Properties of Southern Pine, T. J. Lemoine and P. Koch, 4:34 (No. 4571—$1.50)

Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, H. W. Scheld and R. C. De Groot, 4:33 (No. TN-216—$0.40)

Veneer Yields from Turpentined Slash Pine Peeler Blocks, A Clark III and J. G. Schroeder, 2:53 (No. 4521—$1.00)

Static and Dynamic Properties of Glued Wood-Joist Floors, A. Polensek, 12:31 (No. 4632—$1.50)

Statistical Reliability of Predicting Bending Strength from Strength-Ratio Tables, C. S. Walters, J. K. Guiher, and H. W. Norton, 6:47 (No. 4560—$1.50)

Steam-Bending Properties of Southern Pine, T. J. Lemoine and P. Koch, 4:34 (No. 4571—$1.50)

Stresses in Curved Glued-Laminated Timber Beams: Experimental Study, R. O. Foschi, 7:42 (No. 4562—$1.40)

Structural Design Manual for Furniture, C. A. Eckelman, 11:11 (No. 4353—$0.20)

Structural Fastenings: See Wood Engineering.

Structural Sandwiches: See Glues and Gluing Processes and Wood Engineering.

T

Tensile Strength of Redwood Dimension Lumber I. Relation to Grade and Working Stress, A. P. Schniewind and D. E. Lyon, 7:18 (No. 4574—$1.50)

Tensile Strength of Redwood Dimension Lumber II. Prediction of Strength Values, A. P. Schniewind and D. E. Lyon, 8:45 (No. 4574A—$1.50)

Tension Proof Loading of Finger Joints for Laminated Beams, M. D. Strickler and R. F. Pellerin, 6:19 (No. 4577—$1.20)

Tension Proof Loading of Lam Stock for Laminated Beams, R. F. Pellerin and M. D. Strickler, 5:50 (No. 4536—$1.20)

Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, J. H. G. Smith and A. Kozak, 2:38 (No. TN-205—$0.60)

TIMBER PRODUCTION

Development of a Hardwood Utilization Complex—A New Approach, E. L. Klein, 4:16 (No. 4561—$0.60)

Trafficability Tests of an Articulated Log Skidder, B. Y. Richardson, 1:31 (No. 4500—$0.60)

Torsion Shear Test for Particleboard Adapted to a Universal Testing Machine, R. Gertjejansen and J. G. Haygreen, 11:59 (No. TN-221—$0.40)

Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, H. W. Scheld and R. C. DeGroot, 4:33 (No. TN-216—$0.40)

Trafficability Tests of an Articulated Log Skidder, B. Y. Richardson, 1:31 (No. 4500—$0.60)

Transportation Costs in Oregon for Wood and Bark Residues, P. E. Hyde and S. E. Corder, 10:17 (No. 4568—$1.50)

TREATMENTS AND COATINGS

General

Durability of Water-Resisting Treatments on Wood Siding, A. F. Verrall, 6:57 (No. TN-217—$0.40)

Usefulness of a New Method for Measuring Smoke Yield from Wood Species and Panel Products, J. J. Brenden, 12:22 (No. 4636—$1.40)

Coatings

Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, E. A. McGinnes, Jr., and T. W. Dingeldein, 1:53 (No. 4478—$1.50)

Factors in Converting to 'Super' Finishes, A. W. Riedell, 5:12 (No. 4518—$0.60)

Performance of House Paint on Two Overlays on Cottonwood Siding, G. A. Cooper and S. H. Barham, 3:53 (No. 4546—$0.80)

Selection and Field Testing of Coatings for Exterior Hardboard Products, D. Gluck, 11:24 (No. 4401—$1.20)

Preservation

Climate Index for Estimating Potential for Decay in Wood Structures Above Ground, T. C. Scheffer, 10:25 (No. 4594—$1.40)

Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), H. D. Erickson and A. R. de Freitas, 4:53 (No. 4489—$1.20)

Investigation of the Mechanical Characteristics of Truss Plates on Fire-Retardant Treated Wood, D. H. Percival and S. K. Suddarth, 1:17 (No. 4495—$1.20)

Location of Pentachlorophenol by Electron Microprobe and Other Techniques in Cellon Treated Douglas-fir, H. Resch and D. G. Arganbright, 1:38 (No. 4479—$1.00)

Performance of Eastern Hemlock Wharf Timbers, J. Krzyzewski and J. K. Shields, 3:42 (No. TN-208—$0.40)

Predicting by Sonic Measurements the Strength of Logs and Poles Having Internal Decay, J. E. Breeze and R. H. Nilberg, 5:39 (No. 4390—$1.00)

Wood Minesweepers Are Sound After 15 Years of Service, T. L. Highly, T. C. Scheffer, and M. L. Selbo, 5:46 (No. 4543—$0.60)

U

Usefulness of a New Method for Measuring Smoke Yield from Wood Species and Panel Products, J. J. Brenden, 12:22 (No. 4636—$1.40)

Utilization of Bark in Highway Landscaping, J. Mater, 8:17 (No. 4648—$0.80)

V

Variables in Vacuum Laminating of Thermoplastic Films, T. F. Duncan, 7:30 (No. 4488—$1.50)

Veneer: See Glues and Gluing Processes and Drying.

Veneer Cutting: See Mechanical Conversion.

Veneer Drying Emissions—Problem Definition, D. H. Brown, 9:51 (No. 4719—$0.60)

Veneer Yields from Turpentined Slash Pine Peeler Blocks, A. Clark III and J. G. Schroeder, 2:53 (No. 4521—$1.00)

W

Withdrawal Resistance of Plain and Galvanized-Steel Nails During Changing Moisture Conditions, J. F. Senft and S. K. Suddarth, 4:19 (No. 4530—$1.20)

WOOD ENGINEERING

General

Resistance Strain Gages and Adhesives for Wood, A. Sliker, 12:40 (No. 4623—$0.80)

Wood Engineering Review — 1969, J. F. Senft, 8:21 (No. 4584—$1.50)

Grading

Drying West Coast Dimension to Meet the New Lumber Standards, E. M. Williston, 3:44 (No. 4538—$1.00)

Evaluation of Machine Stress Rating Grades Assigned to Eastern Spruce Structural Lumber, A. M. Brackley and J. E. Shottafer, 4:43 (No. TN-209—$0.80)

Tensile Strength of Redwood Dimension Lumber I. Relation to Grade and Working Stress, A. P. Schniewind and D. E. Lyon, 7:18 (No. 4574—$1.50)

Housing

Durability of Water-Resisting Treatments on Wood Siding, A. F. Verrall, 6:57 (No. TN-217—$0.40)

Elastomeric Adhesives for Field-Gluing Plywood Floors, C. B. Vick, 8:34 (No. 4604—$1.50)

Field Measured Sound Insulation of Wood-Framed Floors, J. B. Grantham and T. B. Heebink, 5:33 (No. 4502—$1.20)

Static and Dynamic Properties of Glued Wood-Joist Floors, A. Polensek, 12:31 (No. 4632—$1.50)

Wood Floor System Is Cost Competitive with Concrete Slab, H. E. Dickerhoof and J. D. Lawrence, 2:13 (No. 4524—$1.20)

Wood Housing: A World-Wide Look, H. O. Fleischer, 12:12 ($0.40)

Mechanical Properties

Bending Strength and Moment-Rotation Characteristics of Two-Pin Moment-Resisting Dowel Joints, C. A. Eckelman, 3:35 (No. 4527—$1.00)

Characterization of the Strength of Juvenile Wood of Loblolly Pine (*Pinus Taeda* L.), R. G. Pearson and R. C. Gilmore, 1:23 (No. 4486—$1.50)

Creep of Wood after Soaking in Liquid Anhydrous Ammonia, D. Green and C. Koch, 11:50 (No. TN-206—$0.40)

Evaluating Particleboard Properties by Measuring Saw-Cutting Force, K. C. Shen, 10:46 (No. 4610—$1.40)

Gamma Irradiation Effects on Modulus of Elasticity of Engelmann Spruce, C. E. Shuler, 7:49 (No. TN-194—$0.60)

High-Temperature Kiln-Drying of Spruce Joists, M. Y. Cech and D. R. Huffman, 10:55 (No. 4598—$1.20)

Investigation of the Mechanical Characteristics of Truss Plates on Fire-Retardant Treated Wood, D. H. Percival and S. K. Suddarth, 1:17 (No. 4495—$1.20)

Nail Withdrawal Resistance in Plantation Red Pine Grown in Indiana, R. H. Perkins, 6:29 (No. 4575—$0.80)

Physical and Mechanical Variations in Cottonwood and Hickory Flakeboards Made from Flakes of Three Sizes, S. Bhagwat, 9:100 (No. 4419—$0.60)

Predicting by Sonic Measurements the Strength of Logs and Poles Having Internal Decay, J. E. Breeze and R. H. Nilberg, 5:39 (No. 4390—$1.00)

Quantitative Study of Some Factors Affecting the Abrasiveness of Particleboard, R. R. Bridges, 11:39 (No. 4494—$0.90)

Rapid Accelerated-Aging Test Procedure for Phenolic Particleboard, K. C. Shen and B. Wrangham, 5:30 (No. 4516—$0.80)

Relationships Between Torsion Shear and Other Strength Properties of Particleboard, K. C. Shen, 6:40 (No. 4484—$0.80)

Statistical Reliability of Predicting Bending Strength from Strength-Ratio Tables, C. S. Walters, J. K. Guiher, and H. W. Norton, 6:47 (No. 4560—$1.50)

Steam-Bending Properties of Southern Pine, T. J. Lemoine and P. Koch, 4:34 (No. 4571—$1.50)

Stresses in Curved Glued-Laminated Timber Beams: Experimental Study, R. O. Foschi, 7:42 (No. 4562—$1.40)

Tensile Strength of Redwood Dimension Lumber I. Relation to Grade and Working Stress, A. P. Schniewind and D. E. Lyon, 7:18 (No. 4574—$1.50)

Tensile Strength of Redwood Dimension Lumber II. Prediction of Strength Values, A. P. Schniewind and D. E. Lyon, 8:45 (No. 4574A—$1.50)

Tension Proof Loading of Finger Joints for Laminated Beams, M. D. Strickler and R. F. Pellerin, 6:19 (No. 4577—$1.20)

Tension Proof Loading of Lam Stock for Laminated Beams, R. F. Pellerin and M. D. Strickler, 5:50 (No. 4536—$1.20)

Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, H. W. Scheld and R. C. De Groot, 4:33 (No. TN-216—$0.40)

Torsion Shear Test for Particleboard Adapted to a Universal Testing Machine, R. Gertjejansen and J. G. Haygreen, 11:59 (No. TN-221—$0.40)

Withdrawal Resistance of Plain and Galvanized-Steel Nails During Changing Moisture Conditions, J. F. Senft and S. K. Suddarth, 4:19 (No. 4530—$1.20)

Wood Engineering Review — 1969, J. F. Senft, 8:21 (No. 4584—$1.50)

Wood Floor System Is Cost Competitive with Concrete Slab, H. E. Dickerhoof and J. D. Lawrence, 2:13 (No. 4524—$1.20)

Wood Housing: A World-Wide Look, H. O. Fleischer, 12:12 ($0.40)

Wood Industries and Research in the Netherlands, K. Griffioen, 5:11 (No. 4659—$0.40)

Wood Industries and Wood Science in Norway, R. Birkeland, 1:10 (No. 4591—$0.40)

Wood Minesweepers Are Sound After 15 Years of Service, T. L. Highly, T. C. Scheffer, and M. L. Selbo, 5:46 (No. 4543—$0.60)

Wood Products Use Trends in FHA-Inspected Single-Family Houses, R. B. Phelps, 7:10 (No. 4556—$0.80)

FPRS Author Index . . . Vol. XXI, 1971

A

Amburgey, T. L., and D. W. French, Plastic Soil Covers Reduce the Moisture Content in Basementless Homes, 8:43 (No. TN-212—$0.40)

Arganbright, D. G., *see* Resch, H.

Atherton, G. H., *see* Corder, S. E.

B

Back, E. L., E. I. E. Didriksson, F. Johanson, and K. G. Norberg, Hot, Dry Mouldability of Hardboard, 9:96 (No. 4595—$1.00)

Barham, S. H., *see* Cooper, G. A.

Barron, E. H., Deterioration of Southern Pine Beetle-Killed Trees, 3:57 (No. 4528—$0.60)

Barton, G. M., *see* Meyer, R. W.

Beall, F. C., *see* Ziegler, G. A.

Bhagwat, S., Physical and Mechanical Variations in Cottonwood and Hickory Flakeboards Made from Flakes of Three Sizes, 9:101 (No. 4419—$0.60)

Birkeland, R., Wood Industries and Wood Science in Norway, 1:10 (No. 4591—$0.40)

Bohrer, D. A., Instrumentation for 'Walsh-Healey' Noise Surveys, 9:88 (No. 4717—$0.40)

Boydston, J. R., Plywood and Sawmill Liquid Waste Disposal, 9:58 (No. 4605—$1.20)

Brackley, A. M., and J. E. Shottafer, Evaluation of Machine Stress Rating Grades Assigned to Eastern Spruce Structural Lumber, 4:43 (No. TN-209—$0.80)

Breeze, J. E., and R. H. Nilberg, Predicting by Sonic Measurements the Strength of Logs and Poles Having Internal Decay, 5:39 (No. 4390—$1.00)

Brenden, J. J., Usefulness of a New Method for Measuring Smoke Yield from Wood Species and Panel Products, 12:17 (No. 4636—$1.40)

Bridges, R. R., Quantitative Study of Some Factors Affecting the Abrasiveness of Particleboard, 11:39 (No. 4494—$0.90)

Brown, D. H., Veneer Dryer Emissions —Problem Definition, 9:51 (No. 4719—$0.60)

C

Cain, S. A., Environment and the Forest Products Industry, 9:16 (No. 4721—$0.60)

Cech, M. Y., Dynamic Transverse Compression Treatment to Improve Drying Behavior of Yellow Birch, 2:41 (No. 4512—$1.50)

Cech, M. Y., and D. R. Huffman, High-Temperature Kiln-Drying of Spruce Joists, 10:55 (No. 4598—$1.20)

Chow, P., C. S. Walters, and J. K. Guiher, pH Measurements for Pressure-Refined Plant-Fiber Residues, 12:50 (No. TN-224—$0.40)

XUM

Chow, S.-Z., Determining Veneer Surface Inactivation by a Reflectance Colorimeter, 2:19 (No. 4515—$1.20)
Clark III, A., and J. G. Schroeder, Veneer Yields from Turpentined Slash Pine Peeler Blocks, 2:53 (No. 4521—$1.00)
Clark, E. L., Plastics and the Future of the Furniture Industry in the United States, 8:14 (No. 4638—$0.60)
Comstock, G. L., Kinetics of Veneer Jet Drying, 9:104 (No. 4597—$1.40)
Cooper, G. A., Black Walnut Extractives Availability is Influenced by Thawing-to-Extraction Time, 10:44 (No. TN-222—$0.40)
Cooper, G. A., and S. H. Barham, Performance of House Paint on Two Overlays on Cottonwood Siding, 3:53 (No. 4546—$0.80)
Corder, S. E., and G. H. Atherton, Improved Performance of Wigwam Burners, 9:40 (No. 4731—$1.50)
Corder, S. E., *see* Hyde, P. E.
Craft, E. P., Construction Grade Plywood from Grade 3 Hardwoods—An Industrial Possibility, 2:26 (No. 4455—$1.00)
Craft, E. P., *see* Cuppett, D. G.
Cuppett, D. G., and E. P. Craft, Low-Temperature Drying of 4/4 Appalachian Red Oak, 1:34 (No. 4475—$1.00)
Currier, R., *see* Scroggins, T. L.
Cutter, B. E., *see* Murphey, W. K.

D

de Freitas, A. R., *see* Erickson, H. D.
DeGroot, R. C., and H. W. Scheld, Biodegradability of Sapwood from Southern Pine Logs Stored Under a Continuous Water Spray, 10:53 (No. 4599—$0.60)
DeGroot, R. C., *see* Scheld, H. W.
Demaree, L., *see* Erickson, R.
Dickerhoof, H. E., and J. D. Lawrence, Wood Floor System Is Cost Competitive with Concrete Slab, 2:13 (No. 4524—$1.20)
Didriksson, E. I. E., *see* Back, E. I.
Dingeldein, T. W., *see* McGinnes, E. A.
Dost, W. A., Redwood Bark Fiber in Particleboard, 10:38 (No. 4592—$1.20)
Duncan, T. F., Variables in Vacuum Laminating of Thermoplastic Films, 7:30 (No. 4488—$1.50)
Dust, J. V., *see* Thompson, W. S.

E

Eckelman, C. A., Bending Strength and Moment-Rotation Characteristics of Two-Pin Moment-Resisting Dowel Joints, 3:35 (No. 4527—$1.00)
Eckelman, C. A., Structural Design Manual for Furniture, 11:11 (No. 4353—$0.20)
Erickson, H. D., and A. R. de Freitas, Influence of Various Molds and Seasoning on Vacuum-Light Oil Treatment of Round Red Alder (*Alnus rubra* Bong.), 4:53 (No. 4489—$1.20)
Erickson, J. R., Bark-Chip Segregation: A Key to Whole-Tree Utilization, 9:110 (No. 4600—$0.80)
Erickson, R., L. Demaree, P. Johnston, and E. Morton, Prefreezing Alone and Combined with Presteaming in the Drying of Redwood Dimension, 7:54 (No. 4579—$1.20)
Espenas, L. D., Shrinkage of Douglas-Fir, Western Hemlock, and Red Alder as Affected by Drying Conditions, 6:44 (No. 4596—$0.60)
Evans, P. G., *see* Wengert, E. M.

F

Fahey, D. J., and D. S. Pierce, Resistance of Resin-Impregnated Paper Overlays to Accelerated Weathering, 11:30 (No. 4603—$1.50)
Fasick, C. A., and J. D. Lawrence, An Operations Research Application to Furniture Round Production, 4:46 (No. 4545—$1.40)
Fisher, C. W., Soil Percolation and/or Irrigation of Industrial Effluent Waters—Especially Wood Treating Plant Effluents, 9:76 (No. 4722—$0.80)
Fleischer, H. O., Wood Housing: A World-Wide Look, 12:12 ($0.40)
Foschi, R. O., Stresses in Curved Glued-Laminated Timber Beams: Experimental Study, 7:42 (No. 4562—$1.40)
Freeman, H. G., and W. C. Grendon, Formaldehyde Detection and Control in the Wood Industry, 9:54 (No. 4672—$0.80)
French, D. W., *see* Amburgey, T. L.
French, D. W., *see* Haygreen, J. G.

G

Gartner, J. B., J. E. Klett, and D. C. Saupe, Hardwood Bark for Packaging of Bare Root Nursery Stock, 6:36 (No. 4564—$1.00)
Gartner, J. B., M. M. Meyer, Jr., and D. C. Saupe, Hardwood Bark as a Growing Media for Container-Grown Ornamentals, 5:25 (No. 4563—$1.00)
Gatchell, C., *see* Murphey, W. K.
Gertjejansen, R., and J. G. Haygreen, Torsion Shear Test for Particleboard Adapted to a Universal Testing Machine, 11:59 (No. TN-221—$0.40)
Gertjejansen, R. O., *see* Stayton, C. L.
Gilmore, R. C., *see* Pearson, R. G.
Gluck, D. G., Selection and Field Testing of Coatings for Exterior Hardboard Products, 11:24 (No. 4401—$1.20)
Good, W. S., Consumer Life Styles and Household Furniture Purchases, 4:11 (No. 4510—$1.00)
Grantham, J. B., and T. B. Heebink, Field Measured Sound Insulation of Wood-Framed Floors, 5:33 (No. 4502—$1.20)
Gray, G. R., *see* Martin, R. E.
Green, D., and C. Koch, Creep of Wood after Soaking in Liquid Anhydrous Ammonia, 11:50 (No. TN-206—$0.40)
Gregersen, H. M., The Latin American Contribution to United States Forest Products Imports: Problems and Potentials for the Exporter, 3:16 (No. 4535—$1.00)
Grendon, W. C., *see* Freeman, H. G.
Griffioen, K., Wood Industries and Research in the Netherlands, 5:11 (No. 4659—$0.40)
Guiher, J. K., *see* Chow, P.
Guiher, J. K., *see* Walters, C. S.

H

Hampf, F. E., *see* Pierson, G.
Harry, J. E., *see* McMillin, C. W.
Hartwig, J. R., Control of Emissions from Batch-Type Charcoal Kilns, 9:49 (No. 4728—$0.40)
Haskell, H. H., Handling Phenolic Resin Adhesive Wash Water in Southern Pine Plywood Plants, 9:64 (No. 4635—$1.20)
Haygreen, J. G., and D. W. French, Some Characteristics of Particleboards from Four Tropical Hardwoods of Central America, 2:30 (No. 4525—$0.80)
Haygreen, J. G., *see* Gertjejansen, R.
Haygreen, J. G., *see* Stayton, C. L.
Heebink, T. B., *see* Grantham, J. B.
Highly, T. L., T. C. Scheffer, and M. L. Selbo, Wood Minesweepers Are Sound After 15 Years of Service, 5:46 (No. 4543—$0.60)
Holemo, F. J., Inventory Management — The Tool and the Need — In Lumber Production, 1:12 (No. 4496—$1.00)
Hse, C.-Y., Properties of Phenolic Adhesives as Related to Bond Quality in Southern Pine Plywood, 1:44 (No. 4485—$1.50)
Huber, H. A., Computerized Economic Comparison of a Conventional Furniture Rough Mill with a New Processing System, 2:34 (No. 4509—$1.00)
Huffman, D. R., *see* Cech, M.Y.
Hyde, P. E., and S. E. Corder, Transportation Costs in Oregon for Wood and Bark Residues, 10:17 (No. 4568—$1.50)
Hyvarinen, M. J., *see* Stayton, C.L.

J

Johanson, F., *see* Back, E. L.
Johnston, P., *see* Erickson, R.
Jones, D. T., Developments in Roll Spreading Techniques, 6:24 (No. 4473—$1.00)

K

Kaiser, Jr., H. F., Productivity Gains in Forest Products Industries, 5:14 (No. 4587—$0.60)
Klein, E. L., Development of a Hardwood Utilization Complex—A New Approach, 4:16 (No. 4561—$0.60)
Klett, J. E., *see* Gartner, J. B.
Koch, C., *see* Green, D.
Koch, P., Force and Work to Shear Green Southern Pine Logs at Slow Speed, 3:21 (No. 4558—$1.20)
Koch, P., Process for Straightening and Drying Southern Pine 2 by 4's in 24 Hours, 5:17 (No. 4569—$1.50)
Koch, P., *see* Lemoine, T. J.
Kotok, E. S., Effect of Resonating Wood During Drying, 2:24 (No. 4451—$0.40)
Kozak, A., *see* Smith, J. H. G.
Kozlik, C. J., Electrical Moisture Meter Readings on Western Hemlock Dimension Lumber, 6:34 (No. TN-218—$0.40)
Krzyzewski, J., and J. K. Shields, Performance of Eastern Hemlock Wharf Timbers, 3:42 (No. TN-208—$0.40)

L

Lamb, F. M., Industrial Noise and Noise Exposure, 9:84 (No. 4627—$0.80)
Lamb, F. M., Industrial Noise Control Guidelines, 11:12 (No. 4725—$1.00)
Lane, P. H., Identifying Veneer in Recovery Studies, 6:32 (No. 4611—$0.40)
Lawrence, J. D., *see* Dickerhoof, H. E.
Lawrence, J. D., *see* Fasick, C. A.
Lemoine, T. J., and P. Koch, Steam-Bending Properties of Southern Pine, 4:34 (No. 4571—$1.50)
Lin, R. T., Economical Humidity Jar, Its Design and Use, 7:51 (No. TN-219—$0.60)
Lombard, D. P., Forest and Forest Products Industry of the Republic of South Africa, 10:14 (No. 4693—$0.60)
Loos, W. E., Fluidized Bed Drying of Southern Pine Veneer, 12:44 (No. 4589—$1.20)
Lyon, D. E., *see* Schniewind, A. P.

M

McAlister, W. R., and H. Resch, Drying 1-Inch Ponderosa Pine Lumber with a Combination of Microwave Power and Hot Air, 3:26 (No. 4550—$1.50)
McGinnes, E. A., Jr., and T. W. Dingeldein, Effect of Light, Extraction, and Storage on Color and Tackiness of Clear-Finished Eastern Redcedar, 1:53 (No. 4478—$1.50)
McKillop, W., Role of Forecasting in the Forest Industries, 8:10 (No. 4619—$0.60)
McMillin, C. W., and J. E. Harry, Laser Machining of Southern Pine, 10:34 (No. 4716—$0.80)
Martin, R. E., and G. R. Gray, pH of Southern Pine Barks, 3:49 (No. 4446—$0.80)
Mater, J., Utilization of Bark in Highway Landscaping, 8:17 (No. 4648—$0.80)
Mergen, A., *see* Peters, C.
Meyer, Jr., M. M., *see* Gartner, J. B.
Meyer, R. W., and G. M. Barton, Relationship Between Collapse and Extractives in Western Red Cedar, 4:58 (No. TN-214—$0.60)
Miller, D. G., Combining Radio-Frequency Heating with Kiln-Drying to Provide Fast Drying without Degrade, 12:17 (No. 4616—$1.00)
Morton, E., *see* Erickson, R.
Murphey, W. K., B. E. Cutter, E. Wachsmuth, and C. Gatchell, Feasibility Studies on Gluing of Red Oak at Elevated Moisture Contents, 8:56 (No. TN-213—$0.80)
Murphey, W. K., *see* Ziegler, G. A.

N

Nilberg, R. H., *see* Breeze, J. E.
Norberg, K. G., *see* Back, E. L.
Norton, H. W., *see* Walters, C. S.

O

Oldham, N. D., *see* Wilcox, W. W.

P

Pearson, R. G., and R. C. Gilmore, Characterization of the Strength of Juvenile Wood of Loblolly Pine (*Pinus Taeda* L.), 1:23 (No. 4486—$1.50)
Pellerin, R. F., and M. D. Strickler, Tension Proof Loading of Lam Stock for Laminated Beams, 5:50 (No. 4536—$1.20)
Pellerin, R. F., *see* Strickler, M. D.
Percival, D. H., and S. K. Suddarth, An Investigation of the Mechanical Characteristics of Truss Plates on Fire-Retardant Treated Wood, 1:17 (No. 4495—$1.20)
Perkins, R. H., Nail Withdrawal Resistance in Plantation Red Pine Grown in Indiana, 6:29 (No. 4575—$0.80)
Peters, C., and A. Mergen, Measuring Wood Surface Smoothness: A Proposed Method, 7:28 (No. 4602—$0.60)
Phelps, R. B., Wood Products Use Trends in FHA-Inspected Single-Family Houses, 7:10 (No. 4556—$0.80)
Pierce, D. S., *see* Fahey, D. J.
Pierson, G., and F. E. Hampf, Harbor Debris Can be Salvaged, 9:79 (No. 4630—$0.60)
Polensek, A., Static and Dynamic Properties of Glued Wood-Joist Floors, 12:31 (No. 4632—$1.50)
Poole, C. I., Fluorocarbon Resin Finishes for Wood Cutting Tools, 3:40 (No. 4498—$0.60)
Porter, A. W., Some Engineering Considerations of High-Strain Band Saws, 4:24 (No. 4570—$1.50)

R

Rammer, H. L., *see* Wilcox, W. W.
Resch, H., and D. G. Arganbright, Location of Pentachlorophenol by Electron Microprobe and Other Techniques in Cellon Treated Douglas-fir, 1:38 (No. 4479—$1.00)
Resch, H., *see* McAlister, W. R.
Richardson, B. Y., Trafficability Tests of an Articulated Log Skidder, 1:31 (No. 4500—$0.60)
Riedell, A. W., Factors in Converting to 'Super' Finishes, 5:12 (No. 4518—$0.60)

S

Saupe, D. C., *see* Gartner, J. B.
Scheffer, T. C., Climate Index for Estimating Potential for Decay in Wood Structures Above Ground, 10:25 (No. 4594—$1.40)
Scheffer, T. C., *see* Highly, T. L.
Scheld, H. W., and R. C. DeGroot, Toughness of Sapwood in Water-Sprayed Longleaf Pine Logs, 4:33 (No. TN-216—$0.40)
Scheld, H. W., *see* DeGroot, R. C.
Schniewind, A. P., and D. E. Lyon, Tensile Strength of Redwood Dimension Lumber I. Relation to Grade and Working Stress, 7:18 (No. 4574—$1.50)
Schniewind, A. P., and D. E. Lyon, Tensile Strength of Redwood Dimension Lumber II. Prediction of Strength Values, 8:45 (No. 4574A—$1.50)
Schroeder, J. G., *see* Clark III, A.
Scroggins, T. L., and R. Currier, Agricultural Uses for Western Redcedar Residues from Shake and Shingle Mills, 11:17 (No. 4634—$1.50)
Selbo, M. L., *see* Highly, T. L.
Senft, J. F., Wood Engineering Review — 1969, 8:21 (No. 4584—$1.50)
Senft, J. F., and S. K. Suddarth, Withdawal Resistance of Plain and Galvanized-Steel Nails During Changing Moisture Conditions, 4:19 (No. 4530—$1.20)
Shen, K. C., Evaluating Particleboard Properties by Measuring Saw-Cutting Force, 10:46 (No. 4610—$1.40)
Shen, K. C., Relationships Between Torsion Shear and Other Strength Properties of Particleboard, 6:40 (No. 4484—$0.80)
Shen, K. C., and B. Wrangham, Rapid Accelerated-Aging Test Procedure for Phenolic Particleboard, 5:30 (No. 4516—$0.80)
Shields, J. K., *see* Krzyzewski, J.
Shottafer, J. E., *see* Brackley, A. M.
Shuler, G. E., Gamma Irradiation Effects on Modulus of Elasticity of Engelmann Spruce, 7:49 (No. TN-194—$0.60)
Siegel, W. C., Logging Roads and the Federal Income Tax, 10:12 (No. 4662—$0.60)
Simpson, W. T., Equilibrium Moisture Content Prediction for Wood, 5:48 (No. 4555—$0.40)
Sliker, A., Resistance Strain Gages and Adhesives for Wood, 12:40 (No. 4623—$0.80)
Smith, J. H., Noise in the Woodworking Industry—A Review of the Literature, 9:82 (No. 4718—$0.40)
Smith, J. H. G., and A. Kozak, Thickness, Moisture Content, and Specific Gravity of Inner and Outer Bark of Some Pacific Northwest Trees, 2:38 (No. TN-205—$0.60)
Stayton, C. L., M. J. Hyvarinen, R. O. Gertjejansen, and J. G. Haygreen, Aspen and Paper Birch Mixtures as Raw Material for Particleboard, 12:29 (No. 4618—$0.40)
Stern, E. G., Potential of Building with Wood in South America, 7:14 (No. 4609—$0.80)
Stewart, H. A., Chips Produced With a Helical Cutter, 5:44 (No. 4253—$0.40)
Strickler, M. D., and R. F. Pellerin, Tension Proof Loading of Finger Joints for Laminated Beams, 6:19 (No. 4577—$1.20)
Strickler, M. D., *see* Pellerin, R. F.
Suchsland, O., Linear Expansion of Veneered Furniture Panels, 9:90 (No. 4586—$1.40)
Suddarth, S. K., *see* Percival, D. H.
Suddarth, S. K., *see* Senft, J. F.

T

Tayelor, F. A., Economics of Technical Improvements or Putting R & D to Work, 10:9 (No. 4686—$0.60)
Thompson, W. S., and J. V. Dust, Pollution Control in the Wood Preserving Industry, Part I. Nature and Scope of the Problem, 9:70 (No. 4729—$1.20)
Tretter, V. J., Jr., Pollution Control Activities at Georgia-Pacific, 9:37 (No. 4617—$0.60)

V

Verrall, A. F., Durability of Water-Resisting Treatments on Wood Siding, 6:57 (No. TN-217—$0.40)
Vick, C. B., Elastomeric Adhesives for Field-Gluing Plywood Floors, 8:34 (No. 4604—$1.50)

W

Wachsmuth, E., *see* Murphey, W. K.
Walters, C. S., J. K. Guiher, and H. W. Norton, Statistical Reliability of Predicting Bending Strength from Strength-Ratio Tables, 6:47 (No. 4560—$1.50)
Walters, C. S., *see* Chow, P.
Walters, E. O., Sorting Southern Pine Green Veneer to Improve Drying Control, 11:52 (No. 4422—$1.50)
Wellwood, E. W., Scheduling and Control of a Douglas-fir Plywood Plant Aided by Linear Programming, 11:42 (No. 4593—$1.50)
Wengert, E. M., and P. G. Evans, Automatic Programing and Control for Steam-Heated Lumber Dry Kilns, 2:56 (No. 4526—$0.80)
Williston, E. M., Drying West Coast Dimension to Meet the New Lumber Standards, 3:44 (No. 4538—$1.00)
Wilcox, W. W., N. D. Oldham, and H. L. Rammer, Bacterial Degradation of Dye Used in Incense Cedar Pencil Slats, 2:50 (No. 4490—$0.60)
Wood Products Sub-Council, Principal Pollution Problems Facing the Solid Wood Products Industry, 9:33 (No. 4720—$0.80)
Wrangham, B., *see* Shen, K.C.
Wu, S.-C., Forest Products in Taiwan, 8:13 (No. 4661—$0.40)

Y

Young, H. E., Preliminary Estimates of Bark Percentages and Chemical Elements in Complete Trees of Eight Species in Maine, 5:56 (No. TN-215—$0.80)

Z

Zerbe, J. I., Forest Products for a Better Environment, 6:16 (No. 4626—$0.60)
Ziegler, G. A., W. K. Murphey, and F. C. Beall, Operational Variables in Press Drying Eastern Hemlock, 10:32 (No. TN-220—$0.60)

XUM